

Latex Sealer 1800

Description:

This is an outstanding waterborne Latex based on Ploy vinyl acetate, it is especially formulated to seal-off new walls, and ceiling as well as old painted surfaces of unknown origin. Thus leaving a sound surface for further painting .

Areas Of Use:

Vinyl Latex Sealer 1800 is excellent to use for interior and exterior surfaces such as cement, concrete, gypsum and previously painted surfaces. Due to the good penetrating behavior to fill the surface porosity. So it can be used to improve the hiding power for the top coats.

Specification Data:

Specific Gravity	1.25 ± 0.5 Kg/L
Viscosity	105 ± 5 KU
Solid by volume	29%
Finish	Flat
Coverage	11 - 13 m ² / L with a thickness on 30 micron due to condition of surface
Drying time for touch	30 min (Touch Dry) at 25C°
Drying time for Recoat	2 hour (Hard dry) at 25C°
Thinner	water
Thinning	Up to 15% only
Washability	More than 5000 cycle
Mode of application	Roller , Brush , air spray or airless spray
Cleaning of tools	Using Water
Flash Point	Non flammable
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. use a suitable solvent for cleaning, old flaking paint or poorly bound surfaces must be removed completely.

New Surfaces:

For cement, concrete and gypsum surfaces should be clean, dry then apply one coat of Latex Sealer 1800.

Old Surfaces:

Surface should be clean by using water & soap several times, then wash with water to insure surface clearance and allow to dry well. Use sanding paper for defected and loose paint surface, to release any imperfection then use one coat of Latex Sealer 1800.

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.