

# Wall Putty

## Description:

Wall Putty is a high grade quality based on latex emulsion, and high solids content to provides excellent smoothing and filling properties to small halls crakes. Ideal for filling joints and pores surfaces which can be applied by putty knife or steel trowel to provided excessive thickness are not applied in application. Wall Putty can be used as a repair filler or for full skim coat application, and can be over coated with solvent or water born coatings.

## Areas Of Use:

Wall Putty is an outstanding product which is used for interior and exterior plaster, concrete, gypsum plaster gypsum and board.

When dry, can be sanded to a smooth finish ready to accept to recoat.

## Specification Data:

Specific Gravity	1.85 ± 0.05 Kg/L
Viscosity	12±2 pois
Solid by volume	57.45%
Finish	Flat
Coverage	2-3 m <sup>2</sup> / kg with a thickness on 100 micron due to condition of surface and tools of application
Drying time for touch	30 min ( Touch Dry ) at 25C°
Drying time for Recoat	2 hours ( Hard Dry ) at 25C°
Thinner	Not advisable
Thinning	Up to 10 % up on need
Washability	More than 5000 cycle
Mode of application	Putty Knife, steel Trowel
Cleaning of tools	Water
Flash Point	Non flammable
Storage	2 Years from date of production

## Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning, old flaking paint or poorly bound surfaces must be removed completely.

## New Surfaces:

### Plaster:

Surface should be treated with diluted Latex Sealer 1800, then allow the surface to dry, apply one or two coats of Latex Wall Putty depending on the surface.

### Wood:

Surface should be prepared by using one coat of diluted Luxury Undercoat 313, then apply one or two coats of Latex Wall Putty.

### Repainting:

Cement surfaces should be cleaned with water and soap, rinse thoroughly with water to insure that the surface, is free from all contaminates then let the surface to dry well for flaks or defect painted surface, use a sanding paper to release it then apply one or two coats of latex wall putty.

## Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.