

Q-Tone

Description:

Based on polyvinyl acetate emulsion. Is high quality interior emulsion paint easy to apply. Exhibits good flow and leveling. Exhibits excellent hiding power and high spreading rate.

Recommended Use:

Suitable for use on interior surfaces including concrete, cement, gypsum and plaster.

Specification Data:

Specific Gravity	1.45 ± 0.05 Kg/L
Viscosity	110 ± 5 Ku
Solid by volume	39 ± 3 %
Finish	Matt
Coverage	10 ± 2 m ² / L due to condition of surface
Drying time for touch	30 min (Touch Dry) at 25C°
Drying time for Recoat	2 hours (Hard Dry) at 25C°
Thinner	Water
Thinning	25% first coat - 10% second coat
Washability	More than 1000 cycle
Mode of application	By roll, brush or spray
Cleaning of tools	Using clean water
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust ...etc, which can result adhesion of the paint to the surface.

New Surfaces:

Apply one coat Sealer 1800 on cement, concrete and gypsum surfaces then two Latex Putty coats. Use two or three coats Q-Tone.

Repainting:

Cement surfaces should be cleaned with water and soap, rinse thoroughly with water insure the surface is free from all contaminates then let the surface to dry well for flakes or defect painted surface use a sanding paper to release it then apply previous item.

Recommendation Paint System:-

Product	No. of coats
Sealer1800	1
Latex Putty	2
Q-Tone	2

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.