

Luxury Enamel Undercoat 313

Description:

Luxury Undercoat 313 is an alkyd resin based, suitable for interior and exterior use, exhibits excellent opacity, adhesion to provide an ideal surface for undercoat.

Areas Of Use:

Used as dual purpose primer and undercoat on most wood with excellent sanding properties to finish the surface with Luxury Super Enamel 900 or Gold Crown 800, suitable to all types of surface (concrete, plaster , metal ... etc) whenever finishing with alkyd paint is required, in case of steel surface should be treated with one coat of primer anti-rust First.

Specification Data:

Specific Gravity	1.4 ± 0.05 Kg/Liter.
Viscosity	85 ±5 K U
Solid by volume	46.15%
Finish	Flat
Coverage	12- 14 m ² / L with a thickness on 30 micron due to condition of surface and tools of application
Drying time for touch	30min (Touch dry) at 25C°
Drying time for Recoat	12 hours (Hard dry) at 25C°
Thinner	Sipes Spirit
Thinning	20% first coat and 10 % second coat
Washability	-
Mode of application	By roll, brush or spray
Cleaning of tools	Using Sipes Spirit
Flash Point	35C°
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning, old flaking paint or poorly bound surfaces must be removed completely.

New Surfaces:

Clean the surface and remove any imperfection, prime the surface with a suitable sealer, then allow surface to dry before painting.

Old Surfaces Repainting:

All surfaces should be properly sanded to remove any loose flaking materials, clean the surfaces first with soap and water followed by rinse water then allow the surface to dry before painting.

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.