

Gold Crown Semi - Gloss 300

Description:

Gold Crown semi-gloss 300 enamel are structural paints based on alkyd resin modified with a thixotropic resin, white non – yellowing and pastel shades decorative enamel for interior use only. It is well suited for both new as well as repainted surfaces. available in white color and a very selected standard colors, a wide range of colors by using a color dispensing machine.

Areas Of Use:

Gold Crown semi gloss 300 enamels can be used indoors on, wood, furniture, walls, cement, steel surfaces, and all types of painting which requires a very hard surface with semi-gloss finish.

Specification Data:

Specific Gravity	1.26 ± 0.05 Kg/L
Viscosity	85 ± 5 KU
Solid by volume	46.69 %
Finish	Semi - Gloss
Coverage	12 – 13 m ² / L with a thickness on 30 micron due to condition of surface and tools of application
Drying time for touch	3 – 4 hours (Touch Dry) at 25C°
Drying time for Recoat	12 hours (Hard dry) at 25C°
Thinning	10 % first coat - 20 % second coat
Thinner	Sipes Spirit
Washability	-
Mode of application	Roller, Brush, air spray or airless spray
Cleaning of tools	Using Sipes spirit
Flash Point	35C°
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning old flaking paint or poorly bound surfaces must be removed completely.

New Surfaces:

Wood, Walls prime with Luxury 313 Enamel Undercoat diluted with Sipes Spirit after sanding and allow surface with an appropriate putty, in case of steel surface should primed with one coat of First anti rust primer, then allow the surface to dry well and apply as indicated above.

Repainting Painted Surfaces: wipe off with crystallized soda. Allow the surface to dry.

System Paint Recommended:

For wood surface		For steel surface		For concrete , cement, gypsum surfaces	
Product	No. of coats	Product	No. of coats	Product	No. of coats
Undercoat 313	1	First	1	Latex Sealer 1800	1
Wall Putty	2	Undercoat 313	1	Wall Putty	2
Undercoat 313	1	Gold Crown 300	2	Undercoat 313	1
Gold Crown 300	2			Gold Crown 300	2

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.