

Gold Crown 800

Description:

Gold crown enamel is a top quality gloss finish based on high quality alkyd resin, it is easy to use, with good hiding power, resist to yellowing. Available in white color and a very selected standard colors.

Areas Of Use:

Gold crown 800 enamel can be used for indoors such as wood, furniture, walls, ceiling and steel work. To provide a very fine surface with good adhesion to the primed surface.

Specification Data:

Specific Gravity	1.12 ±0.05 Kg./Liter
Viscosity	85 ±5 KU
Solid by volume	47.3 %
Finish	Gloss
Coverage	11 - 13 m ² / L with a thickness on 30 micron due to condition of surface and tools of application
Drying time for touch	3 – 4 hours (Touch Dry) at 25C°
Drying time for Recoat	12 hours (Hard dry) at 25C°
Thinner	Sipes spirit
Thinning	20 % first coat and 10 % second coat
Washability	-
Mode of application	By roll, brush or spray
Cleaning of tools	Using Sipes Spirit
Flash Point	35C°
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry , clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning old flaking paint or poorly bound surfaces must be removed completely.

New Surfaces:

Wood surface should be treated by use one coat of thinned Luxury Undercoat 313 allow the surface to dry well apply suitable putty, in case of steel surface should primed with one coat of First anti- rust primer, then let surface to dry well and apply as in the beginning .

Repainting:

For wood, cement, surfaces should be cleaned by use soap with water, then rinse thoroughly water several times, allow to dry well, use a sanding paper to release loose or defected paint surface, flakes. then apply as in the beginning.

For steel surface should be treated with Anti Rust primer First.

System Paint Recommended :

For wood surface		For steel surface		For concrete , cement, gypsum surfaces	
Product	No. of coats	Product	No. of coats	Product	No. of coats
Undercoat 313	1	First	1	Latex Sealer 1800	1
Wall Putty	2	Undercoat 313	1	Wall Putty	2
Undercoat 313	2	Gold Crown 800	2	Undercoat 313	1
Gold Crown 800	2			Gold Crown 800	2

Safety For Use.

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.