

Luxury Super Enamel 900

Description:

Luxury Super Enamel 900 is a top quality gloss finish based on superior alkyd resin with light fast pigments which inhibit changing in color, and give excellent opacity with good weathering stability. available in white color with a nice range of standard colors, easy to choose a wide range of colors by dispensing machine.

Areas Of Use:

Luxury Super Enamel 900 can be used at all surfaces. Its suitable for wood works, furniture, cement, metal and all types of surfaces which requires excellent durability.

Specification Data:

Specific Gravity	1.2 ± 0.01 Kg/L
Viscosity	105 ± 5 KU
Solid by volume	47.69%
Finish	Gloss
Coverage	12-14m ² / L with a thickness on 30 micron due to condition of surface and tools of application
Drying time for touch	3 – 4 hours (Touch dry)
Drying time for Recoat	12 hours (Hard dry)
Thinner	Sipes Spirit
Thinning	20% first coat - 10% second coat
Washability	-
Mode of application	roller, Brush, air spray or airless spray
Cleaning of tools	Using sipes spirit
Flash Point	35C°
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning, old flaking paint or poorly bound surfaces must be removed completely.

New Surfaces:

Wood surface should be treated by use one coat of thinned Luxury Undercoat 313 .

Allow the surface to dry well apply suitable putty, in case of steel surface should primed with one coat of First anti rust primer, then allow the surface to dry well and apply as indicated above.

Repainting:

For wood, cement, surfaces should be cleaned by use soap with water, then rinse thoroughly water several times, allow to dry well. Use a sanding paper to release loose or defected paint surface, flakes. then apply as in the beginning.

For steel surface should be treated with Anti - Rust Primer First.

System Paint Recommended:

For wood surface		For steel surface		For concrete , cement, gypsum surfaces	
Product	No. of coats	Product	No. of coats	Product	No. of coats
Undercoat 313	1	First	1	Latex Sealer 1800	1
Wall Putty	2	Undercoat 313	1	Wall Putty	2
Undercoat 313	1	Luxury Super Enamel 900	2	Undercoat 313	1
Luxury Super Enamel 900	2			Luxury Super Enamel 900	2

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.