

Varno

Description:

Varno Varnish based on good types of polyurethane and alkyd resins. It is an outstanding high gloss and transparent, exhibits excellent drying and good flow properties. Easy to apply, has scratch and abrasion resistance when fully dry. Available in clear, and a wide range of colors by color dispensing machine.

Areas Of Use:

Varno Varnish is suitable for interior and exterior use. It can be used for most kind of wooden substrates. Use on new as well as old floors, furniture, doors, frames and similar surface where a durable finish is desired.

Specification Data:

Specific Gravity	0.91 ± 0.05Kg/L
Viscosity	60 ± 5 KU
Solid by volume	43%
Finish	Gloss
Coverage	10m ² / L with a thickness on 30 micron depending on the type of the surface and tools of application
Drying time for touch	75 min (Touch dry) at 25C°
Drying time for Recoat	4 hours (Hard dry) at 25C°
Thinner	Sipes spirit
Thinning	20% first coat - 10% second coat
Washability	-
Mode of application	Brush, Roller, Air spray or airless spray.
Cleaning of tools	Sipes spirit
Flash Point	35C°
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminants such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning old flaking paint or poorly bound surfaces must be removed completely.

New Surfaces:

No primer is required. If necessary apply one coat of Varno Varnish dilute with 20% Sipes spirit.

Old Surfaces:

Surface must be sanded with a fine sanding paper. Then clear dust and contaminants, then two coats of Varno Varnish.

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.