

Si - Stucco (Marbling)

Description:

Si – Stucco is decorative effect paint applied by modern painting techniques. It is a water based, easy to apply with good adhesion, semi gloss surface properties. It is a pleasant mix of art, ideal for recreating an ancient style of decoration which is called “ Marble Effect “.

Areas Of Use:

Si-Stucco can be used for interior walls, ceilings, wood surfaces when a very fine touch of decoration is need like villa, royals, receptions, restaurants, hotels.

So it can be used to decorate independent on emulsion surface.

Si - Stucco is Independent surface preparation when apply thick layer with excellent filling properties will cover all minor surface imperfection.

Specification Data:

Specific Gravity	2±0,1
Viscosity	12±2 Pois
Solid by volume	57%
Finish	Semi - Gloss
Coverage	2 - 3 m ² / Kg due to Condition of surface and tools of application
Drying time for touch	15 min (Touch dry) at 25C°
Drying time for Recoat	2 hours at (Hard dry) at 25C°
Thinner	No thinning
Thinning	No thinning
Washability	More than 5000 cycle
Mode of application	Putty Knife
Cleaning of tools	Using water
Flash Point	Non flammable
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning, old flaking paint or poorly bound surfaces must be removed completely.

New Surfaces:

Wood Surfaces:

Prepare surface by use one coat of diluted Luxury Undercoat 313, then one coat of Latex Wall Putty and finish preparation with one coat of Si – Tone700, then allow the surface to dry and apply Si- Stucco with Putty knife or steel trowel.

Cement And Gypsum Surface:

Prepare the surface with one coat of Latex Sealer 1800, then one coat of Latex Wall Putty and finish preparation with one coat of Si-Tone 700, then allow the surface to dry and apply Si-Stucco with putty knife or steel trowel.

Old Painted Surfaces:

Wood Surfaces:

Use sanding paper to release any grease or loosing materials, flaks and defected painted surface then prepared surface as on the previous new wood surface.

Cement And Gypsum Surface:

Clean up surface well with water and soap several times, then wash with clean water to insure surface is free, fine, then allow to dry and apply as in previous new cement & gypsum surfaces.

System Of Application:

Apply Si-Stucco after surface preparation - by using Putty knife with a (specified shape) separated by wholes and after during (1 hr) apply another coat in the wholes between the first coat (you can use 2 coats or more of Stucco) then, after 2 hours use the edge of Putty knife to press the whole area to get the fine shade of Stucco application.

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.