

First

Description:

A synthetic primer coating with high red oxide content processing excellent rust inhibiting properties conforms to Egyptian standard. Specially formulated to hold out the gloss in succeeding coats of paint.

Areas Of Use:

For use on exposed metal surfaces indoors or outdoors where a rust inhibitive primer is required, such as structural steel, bridge, tanks, fences, metal casings and windows, ornamental steel.

Specification Data:

Specific Gravity	1.44 ± 0.02 Kg/L
Viscosity	95 K U
Solid	52%
Finish	Semi gloss
Coverage	14 – 16 m ² / kg with a thickness on 30 micron due to condition of surface
Drying time for touch	30 min (Touch Dry) at 25C°
Drying time for Recoat	12 hour (Hard dry) at 25C°
Thinner	Sipes spirit
Thinning	10%
Mode of application	Roller, brush, air spray or airless spray
Washability	-
Cleaning of tools	Using Sipes spirit
Flash Point	35C°
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminants such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning, old flaking paint or poorly bound surfaces must be removed completely.

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.