

Quick Dry Varnish

Description:

A high gloss varnish, it contains a high percentage of solid materials to enhance protection for substrates with good leveling, excellent scratching properties and gloss surface where facilities of painting is not available.

Areas Of Use:

Can be used for interior and exterior wooden and metal surfaces with good drying properties.

Specification Data:

Specific Gravity	0.9 Kg /Liter
Viscosity	60 KU
Finish	Gloss
Coverage	12 – 13 m ² / L with a thickness on 30 micron due to condition of surface
Drying time for touch	30 min (Touch dry) at 25C°
Drying time for recoat	2 hours (Hard dry) at 25C°
Thinner	Sipes spirit
Thinning	20 % first coat – 10 % second coat
Mode of application	Roller, brush, sponge
Cleaning of tools	Using Sipes spirit
Flash Point	26C°
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning old flaking paint or poorly bound surfaces must be removed completely.

Old Painted Surface:

Product	No. of coats
First	1
Quick Dry Varnish	2

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.