

Magic Bond

Description:

Magic Bond with a very special formulation easy to use to provide as immediate key to sound bonding surface even under the most severe conditions. Magic Bond looks white in the container but when dries it to a crystal clear film, when diluting use only clear water.

Areas Of Use:

- 1- When Magic Bond is added to a standard cement admixture it produces a tough, dust free concrete, having greatly increased strength and resistance to wear and tear.
- 2- Magic Bond is principally intended for easy sealing of porous substrates to exhibits excellent surface preparation.
- 3- Excellent adhesive properly specially for wall paper.
- 4- Use as adhesive for all types of wood finishes.
- 5- Magic Bond should be stock well before using and water for thinning if required.

Note: When using Magic Bond as an adhesive the Bond should be made while the adhesive is still wet and tacky.

Specification Data:

Specific Gravity	1.01 Kg /L
Viscosity	1000 – 2000 Poise
Finish	-
Coverage	-
Drying time for touch	15 min (Touch Dry) at 25C°
Drying time for recoat	30 min (Hard dry) at 25C°
Thinner	Water
Thinning	Up to 10 %
Mode of application	Roller, brush
Cleaning of tools	Using water
Storage	2 Years from date of production

Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. use a suitable solvent for cleaning, old flaking paint or poorly bound surfaces must be removed completely.

Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.