

# White Glue

## Description:

Excellent adhesive based on modified polyvinyl copolymer emulsion to give optimal strong bonding and adhesion with the substrate. A milky-white color gives after dry a very good clear layer moisture resistance.

## Areas Of Use:

All interiors uses such as wood, furniture, fiberglass wall paper, asbestoses cement, plywood, laminated floor coverings.

## Specification Data:

Specific gravity	1.01 ± Kg/L
Viscosity	1000 - 2000 Poise
Solid by volume	40 %
Finish	-
Coverage	-
Drying time for touch	15 min ( Touch dry ) at 25C°
Drying time for recoat	30 min ( Hard dry ) at 25C°
Thinner	water
Thinning	Not required – max 10%
Mode of application	Roller, brush
Cleaning of tools	Using water
Storage	2 Years from date of production

## Surfaces Preparation:

The surfaces should be dry, clean and free from contaminates such as grease, oil, dust, which can result in poor adhesion of the paint to the surface. Use a suitable solvent for cleaning old flaking paint or poorly bound surfaces must be removed completely.

## Safety For Use:

- 1- Keep away from direct sunlight with good ventilation.
- 2- Keep out of reach of children and direct flame.
- 3- Avoid eye contact and skin for a long time, if it happened, wash thoroughly with fresh water immediately.